


# EXHIBIT 18



US011785275B2

(12) **United States Patent**  
**Reddy et al.**

(10) **Patent No.:** **US 11,785,275 B2**  
(45) **Date of Patent:** **\*Oct. 10, 2023**

(54) **SYSTEM AND METHOD FOR RECEIVING A TELEVISION SIGNAL**

(71) Applicant: **Entropic Communications, LLC**, New York, NY (US)

(72) Inventors: **Madhukar Reddy**, Carlsbad, CA (US); **Curtis Ling**, Carlsbad, CA (US); **Tim Gallagher**, Carlsbad, CA (US)

(73) Assignee: **Entropic Communications, LLC**, New York, NY (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.  
  
This patent is subject to a terminal disclaimer.

(21) Appl. No.: **17/956,889**

(22) Filed: **Sep. 30, 2022**

(65) **Prior Publication Data**

US 2023/0068514 A1 Mar. 2, 2023

**Related U.S. Application Data**

(63) Continuation of application No. 17/862,946, filed on Jul. 12, 2022, now Pat. No. 11,490,152, which is a (Continued)

(51) **Int. Cl.**  
**H04B 1/16** (2006.01)  
**H04N 21/426** (2011.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **H04N 21/4263** (2013.01); **H04B 1/0014** (2013.01); **H04N 5/455** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ..... H04B 1/16; H04B 1/0014; H04B 1/001; H04N 5/455; H04N 21/426; H04N 21/41; H04N 21/4263

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,280,636 A 1/1994 Kelley et al.

5,590,156 A 12/1996 Carney

(Continued)

**FOREIGN PATENT DOCUMENTS**

EP 2087623 A2 8/2009

**OTHER PUBLICATIONS**

*Entropic Communications, LLC v. Charter Communications, Inc.*  
Civil Action No. 2:22-cv-00125-JRG, Defendants' Invalidity and Subject-Matter Eligibility Contentions.

(Continued)


*Primary Examiner* — Blane J Jackson

(74) *Attorney, Agent, or Firm* — McAndrews, Held & Malloy, Ltd.

(57) **ABSTRACT**

A wideband receiver system comprises a wideband analog-to-digital converter (ADC) module and a digital frontend (DFE) module. The wideband ADC is configured to concurrently digitize a band of frequencies comprising a plurality of desired channels and a plurality of undesired channels. The DFE module is coupled to the digital in-phase and quadrature signals. The DFE module is configured to select the plurality of desired channels from the digitized band of frequencies, and generate an intermediate frequency (IF) signal comprising the selected plurality of desired channels and having a bandwidth that is less than a bandwidth of the band of frequencies, where the generation comprises frequency shifting of the selected plurality of desired channels. The IF signal may be a digital signal and the DFE is configured to output the IF signal via a serial or parallel interface.

**20 Claims, 10 Drawing Sheets**





US 11,785,275 B2

Page 2

Related U.S. Application Data

continuation of application No. 17/587,462, filed on Jan. 28, 2022, now Pat. No. 11,399,206, which is a continuation of application No. 17/217,244, filed on Mar. 30, 2021, now abandoned, which is a continuation of application No. 16/430,506, filed on Jun. 4, 2019, now Pat. No. 10,972,781, which is a continuation of application No. 15/792,318, filed on Oct. 24, 2017, now Pat. No. 10,313,733, which is a continuation of application No. 14/948,881, filed on Nov. 23, 2015, now Pat. No. 9,819,992, which is a continuation of application No. 14/617,973, filed on Feb. 10, 2015, now Pat. No. 9,210,363, which is a continuation of application No. 13/962,871, filed on Aug. 8, 2013, now Pat. No. 9,100,622, which is a continuation of application No. 12/762,900, filed on Apr. 19, 2010, now Pat. No. 8,526,898.

(60) Provisional application No. 61/170,526, filed on Apr. 17, 2009.

(51) Int. Cl.

*H04B 1/00* (2006.01)  
*H04N 5/50* (2006.01)  
*H04N 21/438* (2011.01)  
*H04N 21/454* (2011.01)  
*H04N 21/61* (2011.01)  
*H04N 5/455* (2006.01)

(52) U.S. Cl.

CPC ..... *H04N 5/50* (2013.01); *H04N 21/4382* (2013.01); *H04N 21/4383* (2013.01); *H04N 21/454* (2013.01); *H04N 21/6143* (2013.01); *H04N 21/6193* (2013.01)

(56) References Cited

U.S. PATENT DOCUMENTS

5,705,949 A 1/1998 Alelyunas et al.  
5,768,268 A 6/1998 Kline et al.  
6,253,094 B1 6/2001 Schmutz  
6,262,981 B1 7/2001 Schmutz  
6,282,184 B1 8/2001 Lehman et al.  
6,704,372 B2 3/2004 Zhang et al.  
6,735,421 B1 5/2004 Claxton et al.  
6,760,342 B1 7/2004 Skones et al.  
6,906,498 B2 6/2005 Breuch et al.  
6,920,185 B2 7/2005 Hinson  
6,992,855 B2 1/2006 Ehrlich  
7,095,454 B2 8/2006 Waight et al.  
7,130,576 B1 10/2006 Gurantz et al.  
7,145,972 B2 12/2006 Kumar  
7,167,694 B2 1/2007 Khoini-Poorfard et al.  
7,265,792 B2 9/2007 Favrat et al.  
7,362,178 B2 4/2008 Montemayor et al.  
7,373,125 B2 5/2008 Godambe et al.  
7,421,259 B2 9/2008 Gomez et al.  
7,522,901 B2 4/2009 Dauphinee  
7,542,715 B1 6/2009 Gurantz et al.  
7,599,673 B2 10/2009 Maxim et al.  
8,107,916 B2 1/2012 Gatta et al.  
8,285,240 B2 10/2012 Seendripu et al.  
8,300,681 B2 10/2012 Petrovic et al.  
8,331,886 B2 12/2012 Wang et al.  
8,374,568 B2 2/2013 Seendripu et al.  
8,374,569 B2 2/2013 Seendripu et al.  
8,374,570 B2 2/2013 Seendripu et al.  
8,526,898 B2 9/2013 Reddy et al.  
8,577,319 B2 11/2013 Ling et al.  
8,666,350 B2 3/2014 Vauhkonen  
8,892,225 B2 11/2014 Walsh et al.  
8,909,187 B2 12/2014 Seendripu et al.

9,059,672 B2 6/2015 Ling et al.  
9,100,622 B2 8/2015 Reddy et al.  
9,210,362 B2 12/2015 Reddy et al.  
9,210,363 B2 12/2015 Reddy et al.  
9,225,373 B2 12/2015 Gomez et al.  
9,819,992 B2 11/2017 Reddy et al.  
9,942,598 B2 4/2018 Reddy et al.  
10,313,733 B2 6/2019 Reddy et al.  
10,972,781 B2 4/2021 Reddy et al.  
11,381,866 B2 7/2022 Reddy et al.  
2003/0158614 A1 8/2003 Friel et al.  
2003/0228855 A1 12/2003 Herz et al.  
2004/0058661 A1 3/2004 Hsu et al.  
2004/0110522 A1 6/2004 Reddy et al.  
2005/0040909 A1 2/2005 Waight et al.  
2005/0286562 A1 12/2005 Nakao et al.  
2007/0002961 A1 1/2007 Hctor et al.  
2007/0032220 A1 2/2007 Feher  
2007/0042742 A1 2/2007 Kim et al.  
2007/0098089 A1 5/2007 Li et al.  
2007/0111661 A1 5/2007 Bargroff et al.  
2007/0179649 A1 8/2007 Mitsuno  
2007/0263754 A1 11/2007 Currivan et al.  
2009/0075613 A1 3/2009 Safarian et al.  
2009/0258629 A1 10/2009 Ritchey et al.  
2011/0105068 A1 5/2011 Reddy et al.

OTHER PUBLICATIONS

*Entropic Communications, LLC v. DirecTV, LLC* and *Entropic Communications, LLC v. Dish Network Corp.*, Civil Action No. 2:22-cv-00075-JRG and Civil Action No. 2:22-cv-00076-JRG, Defendants’ P.R. 3-3 Invalidity Contentions.

Appendix A—576 Patent—Additional References and Obviousness Chart.

Appendix B—715 Patent—Additional References and Obviousness Chart.

Ex D1—Invalidity Claim Chart U.S. Pat. No. 9,210,362—Favrat.  
Ex D2—Invalidity Claim Chart U.S. Pat. No. 9,210,362—Li.  
Ex D3—Invalidity Claim Chart U.S. Pat. No. 9,210,362—McNeely.  
Ex D4—Invalidity Claim Chart U.S. Pat. No. 9,210,362—Zhang.  
Ex D5—Invalidity Claim Chart U.S. Pat. No. 9,210,362—Pugel.  
Ex. A1—Invalidity Claim Chart—576 Patent—Ardemagni.  
Ex. A2—Invalidity Claim Chart—576 Patent—Basawapatna.  
Ex. A3—Invalidity Claim Chart—576 Patent—Carnero.  
Ex. A4—Invalidity Claim Chart—576 Patent—Davis 055.  
Ex. A5—Invalidity Claim Chart—576 Patent—Davis 730.  
Ex. A6—Invalidity Claim Chart—576 Patent—Gregoire.  
Ex. A7—Invalidity Claim Chart—576 Patent—Inose.  
Ex. A8—Invalidity Claim Chart—576 Patent—James.  
Ex. A9—Invalidity Claim Chart—576 Patent—Kang.  
Ex. A10—Invalidity Claim Chart—576 Patent—Lovinggood.  
Ex. A11—Invalidity Claim Chart—576 Patent—Mutzig.  
Ex. A12—Invalidity Claim Chart—576 Patent—Petruzzelli.  
Ex. A13—Invalidity Claim Chart—576 Patent—Pugel 200.  
Ex. A14—Invalidity Claim Chart—576 Patent—Williams 419.  
Ex. A15—Invalidity Claim Chart—576 Patent—Williams 873.  
Ex. B1—Invalidity Claim Chart—715 Patent—Ardemagni.  
Ex. B2—Invalidity Claim Chart—715 Patent—Carnero.  
Ex. B3—Invalidity Claim Chart—715 Patent—Davis 055.  
Ex. B4—Invalidity Claim Chart—715 Patent—Davis 730.  
Ex. B5—Invalidity Claim Chart—715 Patent—Fisk.  
Ex. B6—Invalidity Claim Chart—715 Patent—Gregoire.  
Ex. B7—Invalidity Claim Chart—715 Patent—Hicks.  
Ex. B8—Invalidity Claim Chart—715 Patent—Kang.  
Ex. B9—Invalidity Claim Chart—715 Patent—Mutzig.  
Ex. B10—Invalidity Claim Chart—715 Patent—Oishi.  
Ex. B11—Invalidity Claim Chart—715 Patent—Petruzzelli.  
Ex. B12—Invalidity Claim Chart—715 Patent—Williams 419.  
Ex. B13—Invalidity Claim Chart—715 Patent—Williams 873.  
Jeffrey A. Weldon, et al. A 1.75-GHz Highly Integrated Narrow-Band CMOS Transmitter With Harmonic-Rejection Mixers, IEEE Journal of Solid-State Circuits, Dec. 2001, pp. 2003-2015, vol. 36, No. 12, Seattle, Washington.



# US 11,785,275 B2

Page 3

---

(56)

## References Cited

### OTHER PUBLICATIONS

Int'l Search Report and Written Opinion Appln No. PCT/2010/031631 dated Jun. 17, 2010.

Int'l Search Report and Written Opinion Appln No. PCT/2010/031627 dated Jun. 18, 2010.

*Entropic Communications, LLC*, v. *Charter Communications, Inc.*, Civil Action No. 2:22-cv-00125-JRG Plaintiff's Opening Claim Construction Brief, May 9, 2023.

*Entropic Communications, LLC*, v. *Charter Communications, Inc.*, Civil Action No. 2:22-cv-00125-JRG Charter's Responsive Claim Construction Brief, May 23, 2023.

*Entropic Communications, LLC*, v. *Charter Communications, Inc.*, Civil Action No. 2:22-cv-00125-JRG Plaintiff's Reply Claim Construction Brief, May 30, 2023.

*Entropic Communications, LLC*, v. *Charter Communications, Inc.*, Civil Action No. 2:22-cv-00125-JRG Rebuttal Expert Declaration of Richard A. Kramer Ph.D. Regarding Claim Construction, Jun. 12, 2023.

*Entropic Communications, LLC*, v. *Charter Communications, Inc.*, Civil Action No. 2:22-cv-00125-JRG Claim Construction Memorandum Opinion and Order, Jun. 26, 2023.





FIG. 1  
(Prior Art)










FIG. 3






FIG. 4






FIG. 5






FIG. 6






FIG. 7






FIG. 8






FIG. 9






FIG. 10



## US 11,785,275 B2

1

SYSTEM AND METHOD FOR RECEIVING A  
TELEVISION SIGNAL

## PRIORITY CLAIM

This application is a continuation of U.S. patent application Ser. No. 17/862,946 filed on Jul. 12, 2022 (now U.S. Pat. No. 11,490,152), which is a continuation of U.S. patent application Ser. No. 17/587,462 filed on Jan. 28, 2022 (now U.S. Pat. No. 11,399,206, which is a continuation of U.S. patent application Ser. No. 17/217,244 filed on Mar. 30, 2021 (abandoned), which is a continuation of U.S. patent application Ser. No. 16/430,506 (now U.S. Pat. No. 10,972,781) filed on Jun. 4, 2019, which is a continuation of U.S. patent application Ser. No. 15/792,318 (now U.S. Pat. No. 10,313,733) filed Oct. 24, 2017, which is a continuation of U.S. patent application Ser. No. 14/948,881 (now U.S. Pat. No. 9,819,992) filed Nov. 23, 2015, which is a continuation of U.S. patent application Ser. No. 14/617,973 (now U.S. Pat. No. 9,210,363) filed on Feb. 10, 2015, which is a continuation of U.S. patent application Ser. No. 13/962,871 (now U.S. Pat. No. 9,100,622) filed on Aug. 8, 2013, which is a continuation of U.S. patent application Ser. No. 12/762,900 filed on Apr. 19, 2010 (now U.S. Pat. No. 8,526,898), which claims the benefit of priority to U.S. provisional application 61/170,526 filed Apr. 17, 2009. Each of the above referenced documents is hereby incorporated by reference in its entirety.

## BACKGROUND

This invention relates to wideband receiver systems and methods having a wideband receiver that is capable of receiving multiple radio frequency channels located in a broad radio frequency spectrum. In particular, the invention relates to wideband receiver systems that are capable of receiving multiple desired television channels that extend over multiple non-contiguous portions of the broad frequency spectrum and grouping them into a contiguous, or substantially-contiguous, frequency spectrum.

Receivers used to down-convert and selectively filter TV channels are referred to as tuners, and tuners designed to concurrently receive several TV channels are referred to as wideband tuners. Existing tuners for these applications down-convert a swath of channels to an intermediate frequency, which are then sent to a demodulator. Because the swath of channels is not contiguous, this swath includes the desired channels as well as undesired channels. The demodulator employs a high-speed data converter to capture this swath of desired and undesired channels in the digital domain and subsequently filters out the desired channels.

In general, television channels broadcasted over the air or over cable networks are distributed across a broad frequency spectrum. That is, the channel frequencies may not be adjacent to each other. In certain applications such as DVR and picture-in-picture, the receiver system may have to concurrently receive several desired channels that may or may not be contiguous. The wideband receiver requirement poses a trade-off to the system to limit either the dynamic range of the wideband tuner or reduce the bandwidth covered by the tuner so that fewer channels may be received and processed by the demodulator.

FIG. 1 shows a conventional wideband tuner **100**. Tuner **100** may be a direct conversion tuner and includes a low noise amplifier LNA1 having an input terminal coupled to a radio frequency (RF) input signal **102** and an output terminal coupled to a mixer M1. The RF signal may include one or

2

more television channels receiving from a cable network via an RF connector or wirelessly via an antenna. The RF input signal may include the VHF and UHF television channels in a terrestrial television broadcasting system or the CATV channels in cable networks. In order to receive all broadcasted channels present in the RF input signal, LNA1 must necessarily have a wide tuning range, high linearity, and low noise. Mixer M1 is coupled to a synthesizer S1 that can generate an oscillator frequency located around the center of the RF signal. Mixer M1 frequency down-converts the received RF input signal to a more convenient intermediate frequency (IF) band. Tuner **100** includes an amplifier V1 having a programmable gain for amplifying the IF signal, which is then band-pass filtered by a filter F1 before outputting to a demodulator.

In general, the RF signal includes multiple desired channels that are located in non-contiguous portions of a radio frequency spectrum. As shown in FIG. 1, the swath of channels **110** occupies a bandwidth BW1 **120** at an RF center frequency  $f_{rfc}$  **130**. Synthesizer S1 may be tuned to a frequency around the center frequency  $f_{rfc}$  **130** for mixing channels **110** to an intermediate frequency  $f_{ifc}$  **160**, the frequency down-mixed channels **140** are amplified by amplifier V1 and then filtered by F1 to produce a swath of channels **170** centered around frequency  $f_{ifc}$  **160**. In an exemplary application shown in FIG. 1, bandwidth BW1 contains 10 channels. In the case where channels are TV channels that are spaced at either 6 MHz or 8 MHz in most parts of the world, bandwidth BW1 **120** would span from 60-80 MHz, i.e., the down-converted bandwidth at the intermediate frequency would require a bandwidth equal to at least BW1, or at least 80 MHz when such architecture is used. It is noted that in other applications where the desired RF channels are located in the low band such as channels numbers 2 to 6 (VHF in the terrestrial TV broadcast or CATV) and in the high band such as channels numbers 14 to 83 of the UHF TV broadcast or channel numbers 63-158 of the CATV's ultra band, the bandwidth BW1 can be 800 MHz or higher. This wide bandwidth of 800 MHz would require a very expensive digital processing circuitry such as very high-speed analog to digital conversion and high-speed processor in the demodulator.

It is desirable to have wideband receiver systems that can increase the dynamic range without requiring expensive data conversion, filtering and channel selection at the demodulator.

## BRIEF SUMMARY

An embodiment of the present invention includes a wideband receiver system that is configured to concurrently receive multiple radio frequency (RF) channels including a number of desired channels that are located in non-contiguous portions of a frequency spectrum and group the desired channels in a contiguous or substantially-contiguous frequency band at an intermediate frequency spectrum, where the term "substantially-contiguous" includes spacing the desired channels close to each other (e.g. as a fraction of the total system bandwidth, or relative to a channel bandwidth) but with a spacing that can be variable to accommodate the needs of overall system. The term "contiguous" heretofore encompasses "substantially-contiguous." The term "spacing" is referred to as the frequency difference between adjacent channels. The system includes a wideband receiver having a complex mixer module for down-shifting the multiple RF channels and transforming them to an in-phase signal and a quadrature signal in the baseband or low



## 3

intermediate frequency (IF) band. The system further includes a wideband analog-to-digital converter module that digitizes the in-phase and quadrature signals. The digital in-phase and quadrature signals are provided to a digital frontend module that contains a bank of complex mixers that frequency-shift the number of desired channels to a baseband where the desired channels are individually filtered.

The digital frontend module may also include a decimator module that decimates the desired RF channels by a factor M before demodulating them to a digital data stream.

In certain embodiments of the present invention, the wideband receiver system additionally includes an up-converter module having multiple complex up-mixers, each of the complex up-mixers is configured to frequency up-shift each one of the desired RF channels to a sub-portion of an IF spectrum, wherein all sub-portions of the desired channels are adjacent to each another and form a contiguous frequency band in the IF spectrum. The act of frequency shifting the desired channels to the IF spectrum allows the wideband receiver system to directly interface with commercially available demodulators. Allowing the spacing of the desired channels in the contiguous spectrum to be variable allows a system to optimize placement of these desired channels for the purposes of avoiding sensitive portions of the spectrum which may either be vulnerable to spurious signals and interference; or which may generate interference directly or as a harmonic product, to other systems.

In another embodiment of the present invention, a multi-tuner receiver system having two or more tuners is provided to receive multiple desired RF channels that extend over several non-contiguous sub-portions of a broad frequency spectrum and group them into a contiguous frequency spectrum. The multi-tuner system includes at least a first tuner that processes a first sub-portion of the broad frequency spectrum into a first in-phase signal and a first quadrature signal and a second tuner that processes a second sub-portion of the broad frequency spectrum into a second in-phase signal and a second quadrature signal. The multi-tuner receiver system further includes a first analog-to-digital converter module that digitizes the first in-phase and quadrature signals and a second analog-to-digital converter module that digitizes the second in-phase and quadrature signals. In addition, the multi-tuner system includes a first digital frontend module having a first number of complex mixers corresponding to a first number of the desired RF channels located in the first sub-portion of the broad frequency spectrum and a second digital frontend module having a second number of complex mixers corresponding to a second number of the desired RF channels located in the second sub-portion of the broad frequency spectrum. The first digital frontend module frequency shifts the first number of the desired RF channels to a first plurality of baseband signals and the second digital frontend module frequency shifts the second number of the desired RF channels to a second plurality of baseband signals.

The multi-tuner system further includes a first up-converter module having a plurality of N complex mixers, wherein N is an integer value equal to the number of desired channel. The first up-converter module frequency up-shifts the first plurality of the baseband signals to a first portion of an intermediate frequency. In addition, the multi-tuner system includes a second up-converter module that frequency up-shifts the second plurality of the baseband signals to a second portion of an intermediate frequency. The first and the second portions of the intermediate frequency are non-overlapping and located adjacent to each other to form a

## 4

contiguous intermediate frequency (IF) band. The multi-tuner system further includes a digital-to-analog converter that converts the contiguous IF band to an analog waveform signal.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic block diagram of a conventional wideband tuner;

FIG. 2 is a schematic block diagram of a wideband receiver system according to an embodiment of the present invention;

FIG. 3 is a simplified circuit diagram of a complex down-mixer according to an embodiment of the present invention;

FIG. 4 is a simplified schematic block diagram of a wideband receiver system according to another embodiment of the present invention;

FIG. 5 is a simplified circuit diagram of a complex up-mixer according to an embodiment of the present invention;

FIG. 6 is a simplified schematic block diagram of a wideband multi-tuner receiver system according to an embodiment of the present invention;

FIG. 7 is a block diagram illustrating an exemplary digital front end according to an embodiment of the present invention in more detail;

FIG. 8 is a block diagram illustrating an exemplary tiled up-converter module according to an embodiment of the present invention in more detail;

FIG. 9 is a simplified block diagram of a wideband multi-tuner receiver system 900 according to an embodiment of the present invention; and

FIG. 10 is a simplified block diagram of a wideband multi-tuner receiver system 1000 according to another embodiment of the present invention.

## DETAILED DESCRIPTION

FIG. 2 is a schematic block diagram of a wideband receiver system 200 according to an embodiment of the present invention. Wideband receiver system 200 includes a radio front end 210 and a digital front end 230. Radio front end 210 may be a single very wide-band tuner receiver that captures the desired swath of channels located in non-contiguous portions of the spectrum having a frequency bandwidth BW1 120. In this example, the number of available channels in BW1 120 is assumed to be 10 with each channel occupying an 8 MHz bandwidth for a total of 80 MHz. Radio front end 210 is shown as including a low noise amplifier LNA 202 having an input terminal configured to receive an RF input signal 102. In the example shown, RF signal 102 includes four desired RF channels having the respective carrier frequency  $f_{rf1}$ ,  $f_{rf2}$ ,  $f_{rf3}$ , and  $f_{rf4}$  that are located in non-contiguous portions of the wide frequency spectrum BW1. It is understood, however, that spectrum BW1 120 may have any other number of desired frequencies that are not contiguous. LNA 202 has a very low noise figure and very high linearity and a wide tuning range (i.e., very high IIP2 and IIP3 intercept points) to maximize a signal-to-noise-and distortion ratio (SNDR) at the amplifier output. LNA 202 may have a programmable gain to amplify RF signal 102 to adequate voltage levels for mixers M1 211 and M2 221.

Mixers M1 211 and M2 221 may be conventional mixers formed using, for example, differential Gilbert cells. Each of the mixers 211 and 221 multiplies (mixes) an amplified RF



## 5

signal **203** with a respective first oscillator frequency signal **205** and a second oscillator frequency signal **207** to generate an in-phase signal **212** and a quadrature signal **222** that have a phase shift of 90° degree between them. Mixers **211** and **221** are identical so that the amplitude of the in-phase signal **212** and quadrature signal **222** are the same. The first and second oscillator frequencies **205** and **207** are identical and have a 90° degree phase shift generated through a 90° degree phase shifter **P1 206**. Synthesizer **S1** may be a single local oscillator operable to generate the oscillator frequency **205** for converting the receive RF signal **102** to a zero-IF or low-IF band. Synthesizer **S1** can be a coarse (large step) phase locked loop. Synthesizer **S1** can also be programmable to cover the wideband frequency of the analog and digital terrestrial broadcast and/or the cable television system. The RF signal **102** may have relatively uniform signal strength in a cable network. However, its signal strength may extend in several orders of magnitude in a terrestrial broadcast system, thus, LNA **202** and/or mixers **M1 211**, **M2 221** are required to have a relatively high dynamic range to handle the large variations in the signal strength.

In-phase signal **212** and quadrature signal **222** are further amplified and filtered by respective amplifiers **V1 213**, **V2 223** and filters **F1 215**, **F2 225** to generate a filtered in-phase signal **216** and a filtered quadrature signal **226**. Filters **F1 215** and **F2 225** may be passive or active low-pass filters to filter out any unwanted frequency components of the signals **214** and **224** before digitizing them for further processing in digital front end **230**. It is understood that the in-phase path **216** and the quadrature path **226** must have the same amplitude spectrum and maintain a fixed phase relationship, i.e., amplifiers **V1 213**, **V2 223** and filters **F1 215**, **F2 225** must be substantially identical. Because the two paths **216** and **226** are in quadrature, the spectral components from both positive and negative frequencies can be overlaid so that the bandwidth (cutoff frequency) of filters **F1 215** and **F2 225** can be one half of the BW1 bandwidth **120**.

Analog-to-digital converters **ADC1 218** and **ADC2 228** are high-speed (i.e., high sampling rate) converters to maximize the dynamic range. In an exemplary application, radio front end **210** operates as a nominal zero-IF down-mixer so that signals **216** and **226** have a nominal bandwidth **290** equal to one half of the RF signal bandwidth **BW1** thanks to the complex down-mixer architecture. In other embodiment, radio front end **210** operates as a low-IF down-mixer so that the nominal bandwidth **290** of signals **216** and **226** is greater than one half of the bandwidth **BW1**. In practice, the sampling rate of **ADC1 218** and **ADC2 228** is chosen to be higher than the Nyquist sampling requirement, i.e., the filtered analog quadrature signals **216** and **226** may be over-sampled in order to reduce or avoid aliasing of undesired signals into the digitized I and Q signals.

**ADC1 218** generates a digital signal **I 232** that is a digital representation of the analog filtered signal **216**; **ADC2 228** generates a digital signal **Q 242** that is a digital representation of the analog filtered signal **226**. Digital signals **I 232** and **Q 242** are then applied to a bank of **N** complex mixers **250**, wherein **N** is an integer value corresponding to the number of desired RF channels located in the non-contiguous portions of the frequency spectrum **BW1**. It is understood that the number **N** can be any integer value. In one embodiment, **N** can be equal to the number of all available channels that exist in the licensed frequency spectrum to provide system flexibility. In other embodiments, **N** can be equal to the number of all receivable channels within a geographic area. In yet another embodiment, **N** can be an integer value less than the number of receivable channels

## 6

with the geographic area to reduce system costs. In the exemplary embodiment shown in FIG. 2, the number of desired channels is 4. That is, each of the 4 complex mixers **250** mixes in-phase and quadrature signals **232** and **242** with an associated frequency to generate a corresponding baseband, which is then individually filtered, decimated and provided to an associated demodulator.

Each of the **N** complex mixers **250** receives the digital signals **I 232** and **Q 242** from **ADCs 218** and **228** to extract a different one of the desired channels and frequency-shifts the extracted signals to the baseband frequency. Each of the frequency shifted desired channels **252** is filtered by an associated filter module (identified as **260a** to **260n**). In an embodiment, each of the filtered signals **260a** to **260n** may be sent directly to an associated demodulator (identified as **270a** to **270n**) for extracting the original information transmitted in the associated desired channel. In another embodiment, each of the filtered signals **262a** to **262n** is further decimated before providing to a demodulator. A path of digital front end **230** is described in more detail below.

FIG. 3 is a simplified circuit diagram of one of the signal paths **272a** to **272n** of digital front end **230** shown in FIG. 2 according to an embodiment of the present invention. In an embodiment, digital signal **I 232** may be further filtered by a filter **311** to obtain a filtered signal **312**. Similarly, digital signal **Q 242** may be further filtered by a filter **321** to obtain a filtered signal **322**. Thus, digital signals **312** and **322** only contain low-frequency components with undesired high-frequency components being eliminated by respective filters **311** and **321**. It is noted that filtered signals **312** and **322** are interposed between the respective **ADCs 218**, **228** and the bank of **N** complex mixers **250**.

Mixer **300**, which represents one of the **N** complex mixers **250**, includes four multipliers **313**, **315**, **323**, and **325**. Multipliers **313** and **315** multiply the filtered signal **312** with respective  $\cos(\omega_{ci}t)$  and  $\sin(\omega_{ci}t)$  signals and generate respective products **314** and **316**. Similarly, multipliers **323** and **325** multiply the filtered Q signal **322** with respective  $\cos(\omega_{ci}t)$  and  $\sin(\omega_{ci}t)$  signals and generate respective products **324** and **326**. An adder **317** sums the products **314** and **326** to generate a frequency-shifted signal **I 318**. An adder **327** sums the products **324** and **316** to generate a frequency-shifted signal **Q 328**. Basically, complex mixer **300** causes a frequency shift of the filtered components **312** and **322** to respective baseband signals **318** and **328** in the digital domain according to the operation:

$$Y(t)=X(t)*e^{-j\omega_c t} \quad (1)$$

or taken the Fourier transform, we obtain:

$$Y(\omega)=X(\omega-\omega_c) \quad (2)$$

Multipliers **313**, **315**, **323**, and **325** are identical digital multipliers. In an embodiment, a numerically controlled oscillator with quadrature output generates the  $\cos(\Omega_{ci}t)$  and  $\sin(\Omega_{ci}t)$  signals. Numerically controlled oscillators (NCO) can be implemented using a phase accumulator and a look-up table. NCOs are known to those of skill in the art and will not be described herein. The frequency  $\Omega_{ci}$  is so chosen that each one of the desired channels embedded in the digital signals **I 232** and **Q 242** will be downshifted to the baseband. In the given example shown in FIG. 2, the bank of **N** complex mixers will have four complex mixers, each one of the **N** (i.e., four) complex mixers is coupled to an individual NCO having a distinct frequency ( $\Omega_{ci}$ ) so that when mixing the filtered digital I and Q signals **312** and **322** with that frequency, each one of the complex mixers will



generate the signals I (318) and Q (328) of a corresponding one of the desired channels at the baseband.

In an embodiment, baseband signals 318 and 328 are further individually filtered by respective filters 330 and 340 that are identified as one of the filters 260a-n in FIG. 2. Filters 330 and 340 may be band-pass or low-pass filters having a narrow bandwidth equal to the bandwidth of a desired channel. In certain embodiments, filters 330 and 340 can be analog passive or active low-pass or complex band-pass filters such as polyphase filters. In another embodiment, filters 330 and 340 can be digital low-pass filters, such as finite impulse response (FIR) filters to eliminate high frequency components that may be aliased back to the baseband signals I<sub>i</sub> (332) and Q<sub>i</sub> (342) when decimated by subsequent decimator 350.

The reduced sampling rate of the N desired baseband channels will be sent as a serial or parallel digital data stream to a demodulator using a serial or parallel data interface according to commonly known methods, as shown in FIG. 2. This approach provides several advantages over conventional tuner architectures. First, it eliminates the need of expensive data conversion, filtering and channel selection on the demodulator side. Second, it removes undesired channels from the signal path at an early stage, thus relieves the large dynamic range requirement in the demodulator.

FIG. 4 shows a simplified schematic block diagram of a wideband receiver system 400 according to another embodiment of the present invention. Wideband receiver system 400 includes a radio front end 410, a digital front end 430, a tiled up-conversion module 450, and a summing digital-to-analog converter module DAC 470. Radio front end 410 includes a low noise amplifier LNA1 that receives an RF input signal 102 and provides an amplified RF signal 403 to mixers M1 411 and M2 421. Mixer M1 411 is coupled to an oscillator frequency 405 of a synthesizer S1 whereas mixer M2 421 is coupled with the oscillator frequency 405 via a phase shifter P1 406 that generates a 90° degree phase-shift to the oscillator frequency 405. Mixers M1 411 and M2 421 generate respective in-phase signal 412 and quadrature signal 422 that are further amplified by respective amplifiers V1 413 and V2 423. The amplified in-phase and quadrature signals 414, 424 are then filtered by filters F1 415 and F2 425 to eliminate undesired frequency components that would be aliased back to the in-phase and quadrature signals when digitally sampled by subsequent analog-to-digital converters ADC1 418 and ADC2 428. Digital signals I 422 and Q 442 at the input of digital front end 430 are digital representations of the filtered analog in-phase and quadrature signals 416, 426 before the ADCs. Digital front end 430 include a bank of N complex mixers 432 comprising 432a to 432n identical mixers, where N is an integer value corresponding to the number of the desired channels located in non-contiguous portions of the frequency spectrum. Each of the N complex mixers 432a to 432n frequency down-converts signals I 432 and Q 442 to an associated baseband. Each of the frequency down-converted I and Q signals are coupled to respective low-pass, band-pass, or decimating filters 434. In this regard, the radio front end 410 and the digital front end 430 are similar to respective radio front end 210 and digital front end 230 of FIG. 2 that have been described in detail above.

In an alternative embodiment of the present invention, the N filtered and decimated channels 438a to 438n (where indices a to n correspond to the associated number of desired channels) are not provided to a demodulator for demodulation. Instead, the N filtered and decimated channels 438a to 438n are further frequency up-converted to an intermediate

frequency (IF) spectrum. In order to achieve that, the N filtered and decimated channels are coupled to a tiled up-conversion module 450 that includes a bank of N complex up-mixers, where N is an integer value correspond to the number of desired received channels. The N complex up-mixers include identical digital mixers 452a to 452n that will be described further in detail below with reference to FIG. 5. The N up-shifted channels are then filtered by a subsequent bank of channel filters 454 that, in an embodiment, comprises N individual finite impulse response (FIR) filters. The N filtered channels are then digitally combined and converted to the analog domain by a summing digital-to-analog converter module DAC 470. The N up-shifted channels are adjacent to each other and form a contiguous or substantially-contiguous set of channels 475 in the IF spectrum centered around  $f_{if}$  as illustrated in FIG. 4. In an embodiment, the spectra of the mixed products are spaced in such a way so as to avoid overlap with known frequency bands containing potential or actual interferers. In another embodiment, the spectra of the mixed products are spaced in such a way so as to avoid overlap with frequency bands that might introduce interference to other systems. In general, because the bandwidth  $BW_2$  is substantially lower than  $BW_1$ , the IF frequency  $f_{if}$  can be set proportionally lower, e.g., typically about 16 MHz to accommodate the spectrum of  $BW_2$  of up to 32 MHz (corresponding to the total bandwidth of the four desired channels, each having a bandwidth of 8 MHz in this example).

The up-conversion approach of FIG. 4 provides several advantages over conventional tuner architectures. First, it allows the demodulator to operate the data converter at a lower data rate and with lower resolution (fewer bits) due to the fact that the contiguous channels have a narrower bandwidth. Second, the up-conversion approach provides full compatibility with existing demodulators that require an analog IF signal. Third, it removes undesired channels from the signal path at an early stage, thus relieves the requirement of a high dynamic range requirement of the demodulator's analog-to-digital converter and the demodulator itself.

FIG. 5 shows a simplified exemplary circuit diagram of a complex up-mixer 500 according to an embodiment of the present invention. Up-mixer 500 is one of the N complex up-mixers 452a to 452n in tiled up-conversion module 450 shown in FIG. 4. Up-mixer 500 includes filter 510 and 520 configured to eliminate unwanted frequency components present in respective input signals I 501 and Q 502. Filtered signals 512 and 522 are provided to up-mixers UMI 515 and UMQ 525 that multiply the filtered signals 512 and 522 with respective  $\cos(\omega_u t)$  and  $\sin(\omega_u t)$ . The products 516 and 526 are summed in an adder 530 to generate an IF signal 532 according to the following equation:

$$IF(t) = I(t) * \cos(\omega_u t) + Q(t) * \sin(\omega_u t) \quad (3)$$

Up-mixers UMI 515 and UMQ 525 are identical digital multipliers that multiply the respective filtered signal 512 and 522 with a cosine function 505 and a sine function 506 that can be generated from a NCO using a digital phase accumulator and a look-up table.

As described above, TV channels are grouped into multiple frequency bands in North America. For example, channels 2 through 6 are grouped in VHF-low band (aka band I in Europe), channels 7 through 13 in VHF-high band (band III), and channels 14 through 69 in UHF band (bands IV and V). In order to receive such a wide frequency spectrum, the low noise amplifier and mixer must have very low noise, wide tuning range and high linearity as described



above in the wideband receiver systems **200** and **400**. However, a wideband receiver having a single tuner with high sensitivity may have a high power consumption. For certain applications, it may be advantageous to use multiple tuners that are optimized for a given frequency band, such as a dedicated tuner for the low VHF band, another dedicated tuner for the high VHF band and the UHF band, and yet other dedicated tuners for receiving the digital video broadcasting (DVB) via satellite (DVB-S), via cable (DVB-C), or terrestrial digital video broadcasting (DVB-T). The multi-tuner approach may also be advantageously applied to cable networks that carry TV programs on an 88 MHz to 860 MHz according to the Data Over Cable Service Interface Specification (DOCSIS) protocol.

FIG. 6 shows a simplified schematic block diagram of a wideband multi-tuner receiver system **600** according to an embodiment of the present invention. In an embodiment, multi-tuner system **600** includes low noise amplifier **A1 602** for receiving an RF input signal **601**. Amplifier **A1 602** is coupled to at least a tuner **1 610** and a tuner **2 720**. In another embodiment, multi-tuner system **600** may not include amplifier **602** so that RF input signal **601** can be received directly at each tuner **610** and **720**.

Tuner **1 610** includes an amplifying filter **AF1 613** that filters and amplifies a first portion **BWtuner1 604** of a broad frequency spectrum **608** that contains a first plurality of RF channels **606** including desired channels **607** having respective channel frequencies  $f_{rf1}$  and  $f_{rf2}$ . The first portion of the broad frequency spectrum **BWtuner1 604** is then frequency down-converted to a low-IF or zero-IF in-phase signal **I1 612** and a quadrature signal **Q1 622** through respective mixer **M1 611** and **M2 621**. Signals **I1 612** and **Q1 622** are further amplified and low-pass filtered before applying to respective analog-to-digital converters **ADC1 618** and **ADC2 628** that convert analog signals **Ial 616** and **Qa1 626** to respective digital in-phase signal **Id1 631** and digital quadrature signal **Qd1 641**. Because tuner **1 610** only covers a portion **BWtuner1 604** of the entire frequency spectrum **608** having fewer channels, the **ADC1 618** and **ADC2 628** can be slower-speed analog-to-digital converters with a large number of bits, i.e., large dynamic range.

Digital signals **Id1 631** and **Qd1 641** are then provided to a digital front end **DFE 630** that includes a first bank of **N** complex mixers **632** and channel and decimating filters **634**. The first bank of **N** complex filters **632** has **N** identical complex mixers, where **N** is an integer value equal to the number of desired channels located in the first portion **BWtuner1 604** of the broad frequency spectrum **608**. In an embodiment, each one of the first bank of **N** complex mixers includes four digital mixers that multiply digital stream **Id1 631** and **Qd1 641** with respective digitized cosine function and sine function to generate the sum and difference frequency components, as shown in FIG. 3. The digitized cosine and sine frequency, i.e., the mixer frequency is so chosen so that when mixing signals **Id1 631** and **Qd1 641** will move them to a baseband or a low-IF band. In an embodiment, channel and decimating filters have similar structures as filters **330** and **340** and demodulator **350** as shown in FIG. 3. That is, channel and decimating filters include digital low-pass filters **330** and **340** that eliminates unwanted high frequency components of the baseband signals **I** and **Q** prior to applying them to a decimator **350** (FIG. 3) that reduces the sample frequency without any loss of information since **Id1 631** and **Qd1 641** are sampled at a much higher frequency by the respective **ADC1 618** and **ADC2 628**.

The decimated desired channels are then provided to an up-converter module **650** that includes a bank of **N** up-mixers. The bank of **N** up-mixers includes **N** identical up-mixers whose structure is shown in FIG. 5. In an embodiment, **N** is an integer value equal to the number of desired channels present in **BWtuner1 604**. Each one of the up-mixer frequency-shifts the baseband signals **I** and **Q** of each one of the desired channels to an appropriate portion of the intermediate frequency band according to Equation (3). In other words, the bank of **N** up-mixers is “frequency multiplexing” the desired channels onto a first portion **682** of an IF band **686**.

Similarly, tuner **2 720** includes an amplifying filter **AF2 713** that is configured to receive a second portion **BWtuner2 704** of the broad frequency spectrum **608**. The second portion **704** contains a second plurality of RF channels **706** including a second number of desired channels. In the exemplary illustration of FIG. 6, the second portion **704** has a frequency bandwidth of **BWtuner2** that contains desired channels **707** having respective channel frequencies  $f_{rf3}$  and  $f_{rf4}$ . Tuner **2 720** includes elements such as mixers **M3 711**, **M4 721**, amplifiers **V3 714**, **V4 724**, filters **F3 715**, **F4 725** and analog-to-digital converters **ADC3 731** and **ADC4 741** that are substantially the same as the like-named elements of the signal path of tuner **1 610**. Thus, redundant description is omitted herein.

Digital in-phase signal **Id2 731** and digital quadrature signal **Qd2 741** are then provided to digital front end **740**. Digital front end **740** includes a bank of **L** complex filters, where **L** is an integer value equal to the number of desired channels in the second portion **BWtuner2 704** of the broad frequency spectrum **608**. Each one of the bank of **L** complex filters is a digital complex mixer configured to transform the signals **Id2 731** and **Qd2 741** to baseband signals that are further filtered by individual digital low-pass filters such as **FIR** filters before decimated by a subsequent decimator. The elements of digital front end **740** are substantially similar to those described in digital front end **630**. Thus, redundant description is omitted herein.

The decimated baseband **I** and **Q** channels are further provided to a subsequent up-conversion module **760** that performs a function substantially similar to that of the up-conversion module **650** already described above. The outputs of up-conversion module **650** and **760** can be tiled to generate a contiguous set of IF frequencies **682**, **684** centered at  $f_{if}$  **686**. In an embodiment, the outputs of up-conversion module **650** and **760** are digitally summed and converted to an analog signal by summing DAC **670**. In another embodiment, the up-conversion modules **650** and **760** and the digital summing function **672** can be performed using an inverse discrete Fourier transform or an inverse Fast Fourier transform operation.

The multi-tuner architecture provides the flexibility that multiple commercially available tuners can be used without the need of designing a wideband tuner. For example, a tuner designed for a terrestrial broadcast digital TV can be used together with a tuner dedicated to receiving a cable signal and/or a tuner for receiving a satellite broadcast signal. The multi-tuner receiver system provides an additional advantage that other tuners can be added quickly to the system to accommodate any future applications. Additionally, the multi-tuner architecture allows the use of slower speed (i.e., lower cost) analog-to-digital converters with a larger number of bits for achieving large dynamic range.

FIG. 7 shows a block diagram of an exemplary digital front end of the invention in more detail. In an embodiment, in-phase signal **Id2 731** and quadrature signal **Qd2 741** at the



## US 11,785,275 B2

## 11

output of respective ADC converters **718** and **728** are provided to each of the L complex mixers **732** comprising mixers **732A** to **732L**. A more detailed description of each of L complex mixers is shown in FIG. **3**. Mixer **732A** multiplies **Id2 731** and **Qd2 741** with a cosine signal and a sine signal that are generated from an NCO1 and produces an I-**732A** signal and a Q-**732A** signal that are further individually filtered by an FIR filter before decimating. The bank of L complex mixers corresponds to the block **732** in FIG. **6**; and the set of FIR filters and decimator corresponds to the block **734** in FIG. **6**. Each decimated pair of I-**732i/M** in the baseband, where the index “i” is from A to L, is further provided to a subsequent up-mixer for frequency-shifting to an intermediate frequency as shown in FIG. **8**.

FIG. **8** shows an exemplary embodiment of a bank of L complex up-mixers according to the present invention. Each decimated pair of complex signals I-**732i/M** and Q-**732i/M** is provided to an associated complex up-mixer, whose frequency is so chosen that when mixing with the pair of complex signals I-**732i/M** and Q-**732i/M** will generate an associated channel at a predetermined sub-portion of the intermediate frequency band **686** (FIG. **6**). A more detailed schematic block of one of the L up-mixers is described above together with FIG. **5**.

FIG. **9** is a simplified block diagram of a wideband multi-tuner receiver system **900** according to an embodiment of the present invention. In an embodiment, system **900** includes a crossbar switch **910** having at least an input terminal **912** configured to receive signals from an analog-to-digital converter (ADC) **912** and an input terminal **922** configured to receive signals from an ADC **922**. Crossbar switch **910** also includes an output terminal **924** that is coupled to a digital front end **930**. In an embodiment, input terminals **912** and **922** of crossbar switch **910** have P inputs, where P is an integer value that is equal to the total number of desired channels received by tuner1 **610** and tuner2 **720**. Output terminal **924** of crossbar switch **910** have Q outputs, where Q is an integer value that is equal to the total number of desired channels received by tuner1 **610** and tuner2 **720**.

In an embodiment, digital front end **930** may include a bank of R complex mixers that frequency shifts the received channels to a baseband. Digital front end **930** may combine digital front end **630** and **740** shown in FIG. **6**. Similarly, a tiled up-conversion module **950** may include up-converter modules **650** and **760** of FIG. **6**.

System **900** further includes a summing DAC that operates similarly as summing DAC **470** and **670** that have been described in detail in relation with respective FIG. **4** and FIG. **6** above. Thus, redundant description is omitted herein.

FIG. **10** is a simplified block diagram of a wideband multi-tuner receiver system **1000** according to another embodiment of the present invention. System **1000** includes at least tuner1 **610** coupled with digital front end **630** through an analog-to-digital converter **620** and tuner2 **720** coupled with digital front end **740** through an analog-to-digital converter **730**. System **1000** further includes a crossbar switch **1010** that is interposed between digital front ends **630**, **740** and up-conversion modules **650**, **760**. Crossbar switch **1010** includes an input terminal **1012** having S inputs coupled with DFE **630** and an input terminal **1022** having T inputs coupled with DFE **740**. In an embodiment, S is an integer value equal to the number of desired channels processed in DFE **630** and T is an integer value equal to the number of desired channels processed in DFE **740**. Crossbar switch **1010** further includes an output terminal **1024** having U outputs coupled with up-converter module **650** and an output terminal **1024** having V outputs coupled with up-

## 12

converter module **760**. In an embodiment, the total number of the outputs U and V is equal to the sum of the inputs S and T. Thus, crossbar switch **1010** allows the routing of any channel from either DFE **630** or DFE **740** to up-converters **650** or **760**. It is understood that system **1000** is not as flexible as system **900** because DFE **630** and DFE **740** are already pre-assigned to respective tuner1 (**610**) and tuner2 (**720**). However, this pre-assigned arrangement allows a simpler implementation of crossbar switch **1010** that operates at lower speeds.

While several embodiments in accordance with the present invention have been described, it is to be understood that the above description is intended to be illustrative and not restrictive. Many embodiments will be apparent to those of skill in the art upon reviewing the above description. The scope of the invention should, therefore, be determined not with reference to the above description, but instead should be determined with reference to the appended claims along with their full scope of equivalents.

What is claimed is:

1. A method for operating a television receiver, comprising:
  - receiving, by an input terminal, an input signal comprising broadcast channels, the broadcast channels comprising a plurality of desired channels and a plurality of undesired channels, wherein the plurality of desired channels are non-contiguous;
  - processing, by a radio front end coupled to the input terminal, the input signal to generate a processed input signal;
  - digitizing, by an analog-to-digital converter (ADC) coupled to the radio front end, the processed input signal to generate a digitized signal;
  - selecting, by a digital frontend (DFE) coupled to the ADC, the plurality of desired channels from the digitized signal; and
  - outputting, by the DFE, the selected plurality of desired channels to at least one demodulator as a digital datastream, wherein the demodulator extracts information encoded in the digital datastream.
2. The method of claim 1, wherein the DFE outputs the digital datastream via a serial interface.
3. The method of claim 1, wherein the DFE outputs the digital datastream via a parallel interface.
4. The method of claim 1, wherein the ADC comprises:
  - a first ADC configured to generate a digital in-phase signal; and
  - a second ADC configured to generate a digital quadrature signal.
5. The method of claim 1, wherein the extracted information is stored for use in a digital video recorder (DVR).
6. The method of claim 1, wherein the extracted information is output for a picture-in-picture display.
7. The method of claim 1, wherein the plurality of desired channels comprises at least one television channel.
8. The method of claim 1, wherein the plurality of undesired channels comprises at least one television channel.
9. The method of claim 1, wherein the broadcast channels comprise satellite broadcast channels.
10. The method of claim 1, wherein the broadcast channels comprise cable broadcast channels.
11. A television receiver device, comprising:
  - an input terminal operable to receive an input signal comprising broadcast channels, the broadcast channels comprising a plurality of desired channels and a plu-



## US 11,785,275 B2

## 13

ality of undesired channels, wherein the plurality of desired channels are non-contiguous;  
a radio front end, coupled to the input terminal, operable to process the input signal;  
an analog-to-digital converter (ADC), coupled to the radio front end, operable to digitize the processed input signal to generate a digitized signal; and  
a digital frontend (DFE), coupled to the ADC, operable to select the plurality of desired channels from the digitized signal and output the selected plurality of desired channels to at least one demodulator as a digital datastream, wherein the demodulator is operable to extract information encoded in the digital datastream.

12. The television receiver device of claim 11, wherein the DFE is operable to output the digital datastream via a serial interface.

13. The television receiver device of claim 11, wherein the DFE is operable to output the digital datastream via a parallel interface.

14. The television receiver device of claim 11, wherein the ADC comprises:

## 14

a first ADC configured to generate a digital in-phase signal; and  
a second ADC configured to generate a digital quadrature signal.

15. The television receiver device of claim 11, wherein the extracted information is stored for use in a digital video recorder (DVR).

16. The television receiver device of claim 11, wherein the extracted information is output for a picture-in-picture display.

17. The television receiver device of claim 11, wherein the plurality of desired channels comprises at least one television channel.

18. The television receiver device of claim 11, wherein the plurality of undesired channels comprises at least one television channel.

19. The television receiver device of claim 11, wherein the broadcast channels comprise satellite broadcast channels.

20. The television receiver device of claim 11, wherein the broadcast channels comprise cable broadcast channels.

\* \* \* \* \*